



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

UHV gate valve, Series 108, DN 250 (ID 10'')
Ordering No. 10848-CE01

Description

Flange	CF-F 250
Actuator	manual, handwheel
Feedthrough	Bellows

Technical data

Leak rate	- Valve body	$< 5 \cdot 10^{-10}$ mbar ls ⁻¹
	- Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-10}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		19 990 ls ⁻¹
Cycles until first service		50 000 (unheated and under clean conditions)
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve Body	≤ 250 °C open / ≤ 200 °C closed (bake-out max. 24h)
	- Actuator	≤ 250 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	- Valve Body	AISI 304 (1.4301)
	- Mechanism	AISI 316L (1.4404), AISI 304 (1.4301)
	- Bellows	AISI 316L (1.4404, 1.4435)
Seal	- Bonnet	metal
	- Gate	FKM (Viton®), O-ring
Mounting position		any
Weight		52 kg / 114 lbs

Created by: SON	Release date: 2013-01-09	1 of 1
Modified by:	Release date:	298659EA