



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**HV angle valve**  
**Series 264, DN 16 (ID 5/8")**  
**Ordering No. 26424-KA01-0001**

### Description

Flange	ISO-KF 16
Actuator	Manual actuator
Feedthrough	Bellows

### Technical data

Leak rate	- Valve body	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
	- Valve seat	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
Pressure range		$1 \cdot 10^{-8} \text{ mbar to } 5 \text{ bar (abs)}$
Differential pressure on the plate	- In opening direction	$\leq 2 \text{ bar}$
	- In closing direction	$\leq 5 \text{ bar}$
Differential pressure at opening		$\leq 1 \text{ bar}$
Conductance (molecular flow)		$5 \text{ ls}^{-1}$
Cycles until first service (Tmax 80 °C, under clean conditions)		10 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve body	$\leq 150 \text{ °C}$
	- Hand wheel	$\leq 120 \text{ °C}$
Material	- Valve body	Aluminum (EN AW-6060)
	- Hand wheel	Plastic
	- Plate	AISI 316L (1.4435 ESU)
	- Bellows	AISI 316L (1.4404, 1.4435), AISI 316 Ti (1.4571)
Seal	- Bonnet O-ring	FKM (Viton®)
	- Plate O-ring	FKM (Viton®)
	- Actuator O-ring	FKM (Viton®)
Weight		0.25 kg / 0.55 lbs
Mounting position		any

Created by: WARO	Release date: 11.04.2014	1/1
Modified by:	Release date:	<b>745498EA</b>