



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

UHV angle valve
Series 284, DN 16 (ID 5/8")
Ordering No. 28424-GE01-0002

Description

Flange	CF-R 16
Actuator	Manual actuator
Feedthrough	Bellows

Technical data

Leak rate	– Valve body	$\leq 5 \cdot 10^{-10}$ mbar ls ⁻¹
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-10}$ mbar to 5 bar (abs)
Differential pressure on the plate	– In opening direction	≤ 2 bar
	– In closing direction	≤ 5 bar
Differential pressure at opening		≤ 1 bar
Conductance (molecular flow)		5 ls ⁻¹
Cycles until first service		10'000 (T _{max} 80°C; differential pressure max 1bar)
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body	≤ 150 °C
	– Hand wheel	≤ 120 °C
Material	– Valve body	AISI 304 (1.4301)
	– Hand wheel	Plastic
	– Plate	AISI 316L (1.4435 ESU)
	– Bellows	AISI 316L (1.4404, 1.4435), AISI 316 Ti (1.4571)
Seal	– Bonnet seal	Metal
	– Plate O-ring	FKM (Viton®)
Weight		0.34 kg / 0.75 lbs
Mounting position		any

Created by: WARO	Release date: 07.03.2016	1/1
Modified by:	Release date:	823902EA